The Urban Range Sliding/Stacking Door





Flexible and versatile in design, sliding/stacking doors can be manufactured to specific requirements, whether it be a 2, 3 or 4 panel standard sliding/stacking door or 3 and 6 panel sliding/stacking door. Suitable for both residential or apartment living, they are perfect for alfresco living, providing an abundance of natural light and giving a feeling of space. High quality rollers allow ease of sliding for all panels and quality door locks will give you peace of mind in the security of your home. These doors can also be integrated with insect or security screens.

The Urban Sliding/Stacking Door

The new Urban Sliding/Stacking Door offers a high degree of design flexibility. Complemented with high quality hardware plus excellent structural and weather performance, the Urban Sliding/Stacking Door has been designed to suit Australia's wide range of climatic conditions. Integrated insect or barrier screening options and double glazing capabilities ensure the Urban Sliding/Stacking Door can be tailored to your exacting requirements.

As part of the Capral Urban Residential Range, it can be integrated with a complementary selection of sliding, casement, awning and double hung windows to provide a total window solution.

Features and Benefits:

- 101.6mm Framing System
- Single and double glazed options
- Standard configurations (XO, OXO and OXXO)
- Multistack configurations (XXO or OXXXXO)
- Inside and outside corner configurations (OXXcXXO)
- Dedicated double glaze sections
- Highlight option available on selected configurations
- Standard and low profile sill options
- Self draining sill design
- Integrated insect and security screening options
- Custom design hardware options
- Standard and mortice lock options
- Cavity slider options
- Corner sliding configuration options

584 Sliding Door 584 Stacking Door Maximum Recommended Panel Sizes Height 2700mm 2700mm Width 1200mm STD 1200mm STD 1500mm HD 1500mm HD Weight 160kg 160kg Frame Dimensions (Depth & Height) Option 1 Sill 101.6 x 50 STD 101.6 x 50mm STD Option 2 Sill 101.6 x 62 HP 101.6 x 19mm LP **Maximum Product Performance** SLS (Pa) 2500 3000 ULS (Pa) 6000 5500 WATER (Pa) 450 300 **Glazing Details** Single Glazed 4mm - 10mm 4mm - 10mm Double Glazed 16mm & 18mm 16mm - 18mm Maximum Acoustic Rating Rw 30 53* C:CTR -1:-2 -2:-7 Compatible with Urban Residential Range AGS Commercial Range * Secondary glazed configurations.

